

24171

B. Tech. 4th Semester (ME) F. Scheme Examination,
May-2014

STRENGTH OF MATERIALS-I

Paper-ME-206-F

Time allowed : 3 hours]

[Maximum marks : 100

Note : Q. No. 1 is compulsory. Attempt any five questions selecting at least one question from each section.

1. (a) Explain Hook's law. $2.5 \times 8 = 20$
(b) Define modulus of resilience.
(c) What do you mean by positive shear force and negative shear force ?
(d) What is most important assumption in a composite beam ?
(e) What do you mean by equivalent length of a column ?
(f) What are the drawbacks of Euler's theory of buckling ?
(g) What is conjugate beam ?
(h) What are concentrated load ?

(2)

24171

changed so that the stress in each wire is increased by 10N/mm^2 . Find the change of temperature ?

$$E_s = 205,000\text{N/mm}^2, E_c = 102,000\text{N/mm}^2; \\ \alpha_s = 11 \times 10^{-6} / ^\circ\text{C}; \alpha_c = 18 \times 10^{-6} / ^\circ\text{C}. \quad 20$$

3. Draw and describe Mohr's circle.

If, at a point in a material, the minimum and maximum principal stresses are 30N/mm^2 and 90N/mm^2 , both tensile, find the shear stress and normal stress on a plane through this point making an angle of $\tan^{-1} 0.25$ with the plane on which maximum principle stress acts. 20

Section-B

4. A beam ABC, 20m long is simply supported at A and B, 15m apart and carries a load of 18kN at 6m from A inclined at 60° towards A together with a distributed load which is increasingly linear from zero at A to 10 kN/m at B. Draw the SF and BM diagram and calculate the magnitude and location of the maximum bending moment. 20

(3)

24171

Section-C

6. A beam of I-section $400\text{mm} \times 200\text{mm}$ has a web and flange thickness 20mm . Calculate the maximum intensity of the shear stress across this section and sketch the shear stress distribution across the section of the beam, if it carries a shearing force of 300 kN at a section. 20
7. A 3 m long steel bar of rectangular section of $30\text{mm} \times 20\text{ mm}$ is used as a strut with both end hinged. Assuming that Euler's formula is applicable and the material attains its yield strength at the time of buckling, determine the central deflection $E = 205,000\text{N/mm}^2$. Yield strength of steel is 320 N/mm^2 . 20

Section-D

8. Compare the crippling load given by Euler's and Rankine's formulae for a tubular steel strut 2.3m long having outer and inner diameter of 58mm and 35mm ,

9. A simply supported beam has a span of 15m and carries two point loads of 4kN and 9kN at 6m and 10m respectively from one end. Find the deflection under each load and the maximum deflection.

Take $E = 200 \text{ GPa}$ and $I = 400 \times 10^{-6} \text{ mm}^4$.

20