Total No. of Questions: 09

B.Tech.(CE) (Sem.-6th)

DESIGN OF CONCRETE STRUCTURES-II

Subject Code : CE-310

Paper ID: [A0622]

Time: 3 Hrs.

Max. Marks: 60

INSTRUCTION TO CANDIDATES :

- SECTION-A is COMPULSORY consistion of TEN questions carrying TWO marks each.
- SECTION-B contains FIVE questions carrying FIVE marks each and students has to attempt any FOUN questions.
- 3. SECTION-C contains THREE exestions carrying TEN marks each and students has to attempt any TEN questions.

SECTION-A

l. Write briefly:

- a. Explain the type of stresses in symmetrical dome structures.
- b. Give two examples of curved beams and discuss the type of stress resultants encountered in these beams.
- c. Discuss 'Strap Footing' and under what conditions it is provided.
- d. How is the reinforcement provided in cylindrical beams resting on edge beams? Show diagrammatically.
- Outline the analysis and design conditions of an underground water tank.
- f. Discuss some of the common causes of failures in foundations.
- g. Explain the stability criteria of a retaining wall.
- h. Explain the analysis and design criteria of a counterfort in a retaining wall.
- Discuss minimum reinforcement criteria in floors and walls of water tanks.
- Discuss the main components of an Intze Tank.

SECTION - B

- Design a semicircular beam supported on three equally spaced columns.
 The centres of columns are on a circular curve of diameter 9 m. The superimposed load on beam is 25 kN/m. Use M20 concrete and Fe415 steel. Show the design details.
- 3. Describe the design criteria for all the components of a counterfort retaining wall.
- 4. Design a square spread footing to carry a column load of 1000 kN from a 40 cm square tied column containing 20 mm bars as longitudinal steel. The bearing capacity of the soil is 150 kN/m². Consider base of the footing 1 meter below the ground level. The unit weight of earth is 20 kN/m³. Use M20 concrete and Fe415 steel and the load factor is 1.5.
- Design a spherical dome for hall 10 metres in diameter. Rise of dome is 2 meters. Live load and finish load on the dome is 0.75 kN/m² and 0.25 kN/m² respectively. Use M20 and Fe250 steel.
- Discuss in detail, the design and construction criteria to be followed for roofs, walls and joints of water tanks as per IS codal provisions.

SECTION - C

- Design a rectangular combined footing for two columns 450mm × 450mm and 600mm × 600mm carrying 1000 kN and 1200 kN respectively. The columns are located 4.0 m apart. The safe bearing capacity of the soil is 150 kN/m². Use M20 concrete & Fe 250 steel.
- 8. Design a cantilever retaining wall to retain a level earthfill of 4 m above ground level. The surcharge on the earth fill is 18 kN/m². The angle of repose of soil is 30°, unit weight of the soil is 16 kN/m³, coefficient of friction between soil and concrete is 0.6 and the safe bearing capacity of soil is 200 kN/m². Use M20 concrete and Fe250 steel.
- Design a circular tank for a capacity of 40,000 litres of water with flexible base i.e. walls and base slab are not monolithic with each other. Use depth of tank as 4 meters. Use M20 and tor steel as reinforcement.