

Unit-I☒ System of Sewage :-

The water carriage system can be divided into the following types :-

- 1) Separate System
- 2) Combined System
- 3) Partially Separate System

1) Separate System :-

- It provides two separate systems of sewers - the one intended for the conveyance of foul sewage only, such as domestic wastewaters and the other for the rain water, including the surface washing from certain streets, overflow from public latrines and foundations etc.
- The sewage from the first system of sewers can be led to the treatment works, while the flow from the second system of sewers can be discharged directly to natural streams etc without any treatment.

Advantages :-

- (a) The cost of installation is low
- (b) The load on the treatment units will be lowered.
- (c) The sewages will be of more uniform character.
- (d) There is no necessity of providing automatic flushing tanks, for use in dry weather.
- (e) Rain water can be discharged into streams or rivers without any treatment.

Disadvantages :-

- (a) Since the sewers are of small size, it is difficult to clean them.
- (b) They are likely to get choked.
- (c) Two sets of sewers may ultimately prove to be costly.
- (d) Storm water sewers or drains comes in use only during the rainy season.
- (e) Because of lesser air contact in small size sewers, foul smell may be there due to the sewage gas formed.

(iii) The st
dille

(iv) There i
smalle

Disad

(i) The co

(ii) Becau

handli

(iii) During

and m

and

(iv) Storm

(v) The lar

proper

(vi) Large

ventil

3) Partic

• In this

sewer

• These

the ear

• As s

certan

is thir

to the

2) Combined System :-

- This provides only one sewer to carry both the foul sewage as well as the rain water.
- The sewage and rain water are carried to the sewage treatment plant, before its final disposal.
- This is advocated on the ground that the street surface washings are as impure as the sewage itself, and should therefore be suitably treated before being allowed to enter the natural stream.

Advantages :-

- (i) The system requires only one set of sewers. Hence, the maintenance cost is lowered.
- (ii) The sewers are of larger size, and therefore the chances of their ~~etc~~ choking are rare. Also, it is easy to clean them.

e, it is

It
ately prove.

in use only

11 size sewers,
sewage

very both
in water.

carried to the
to final disposal
at the street

the sewage
tably treated
natural stream

of sewers.

lowered.

Therefore the
re. Also, it

(iii) The strength of the sewage is reduced by
dillution.

(iv) There is more air in the larger sewers than in
smaller ones of the separate system.

Disadvantages:->

(i) The cost of construction are very high

(ii) Because of larger size of sewers, their
handling and transportation is difficult.

(iii) During heavy rains, the sewers may overflow,
and may thus create unhygienic conditions
and cause pollution problems.

(iv) Storm water is unnecessarily polluted.

(v) The large sewers get easily silted if not
properly designed.

(vi) Large sewers are more difficult to be
ventilated than the smaller ones.

3) Partially Combined System:->

• In this system, only one set of underground
sewers is laid.

• These sewers admit the foul sewage as well as
the early washings by rains.

• As soon as the quantity of storm water exceeds a
certain limit, the storm water overflows, and
is thus collected and conveyed in open drains
to the natural streams.

• The foul sewage, however, continues to the flow in the sewers.

Advantages:-

- i) The sewers are of reasonable size. Their cleaning is not very difficult.
- ii) It combines the advantage of both the separate as well as the combined systems.
- iii) The storm water permitted in the sewers eliminates its chances of chocking.
- iv) The problem of disposing off storm water from homes is simplified.

Disadvantages:-

- 1) During the dry weather, when there is no rain water, the velocity of flow will be low.
- 2) The storm water increases the load is on treatment units.
- 3) The storm water also increases the cost of pumping.

Factors governing choice of separate system:-

- (a) Financial aspects (b) Flat topography
- (c) Rainfall Pattern (d) Outlet conditions
- (e) Pumping aspects (f) Steep topography
- (g) Subsoil conditions (h) Development pattern

• Com

(a) St

(b) In

(c) Ev

(d) Pu

• The

two

(a) T

(b) S

• Dry

• It is

through

water

• The a

as. S

the f

(i) Don

A cent

daily

domes

varioi

react

the se

is use

ues to the

ize. Their
L.

the separate

ms-

sewers

ng

water

re is no

will be low-

oad is

the

barate

ography

ditions

ography

ent pattern

Combined System:

- (a) Space considerations (H) etc
- (b) Integrated development
- (c) Even rainfall pattern
- (d) Pumping requirements

✳ The total wastewater flow can be divided into two components:

- (a) Dry weather flow (D.W.F)
- (b) Storm water flow or Runoff

✳ Dry Weather flow: →

• It is that quantity of wastewater that flows through a sewer in dry weather when no storm water is in the sewer.

• The dry weather flow is also sometimes called as 'Sanitary Sewage', and is obtained from the following sources:

(i) Domestic Wastewater: →

A certain quantity of water is being supplied daily by the Water Works Department for domestic use. This water gets consumed in various ways, and therefore all of it does not reach the sewer. The wastewater reaching the sewers will be that part of water which is used for flushing water closets, etc.

(ii) Industrial Wastewater :->

This is the wastewater generated by the industry after consuming water for its manufacturing processes.

(vi) C
Estin

(iii) Waste Water from public facilities :-

This is the wastewater from schools, cinema, hotels, railways stations, street washings.

Varia

• The sta
• The va
several

(iv) Ground Water infiltration :

Depends upon the soil type, material of sewers, nature and condition of sewer joints, depth of sewer and position of water table.

working
timings

• In the
rises &
between
rises

Factors Affecting Dry Weather Flow :-

- (i) Rate of water supply
- (ii) Population growth → Arithmetic & all methods
- (iii) Type of area served
- (iv) Infiltration of ground water

• The se
of sew
(i) Be

(ii) Har

(b) Storm Water Flow :->

Runoff or storm water flow depends upon the following factors:

- (i) Catchment area
- (ii) Ground slope
- (iii) Permeability of ground
- (iv) Extent of impervious area
- (v) Rainfall duration

Where,
• S_p
• S_c
• S_f

• The fi
 $P = 1000$
• These

ed by the
for its

(vi) Climatic factors

Estimated by (a) Rational Method

(b) Empirical Method

▣ Variations in Rate of Sewage :->

ies:-

ools, cinema,
t washings.

terial of
A sewer
ition of

- The rate of sewage flow is not constant.
- The variations in the flow may be due to several factors, such as habits of the people, working hours of the office, climatic conditions, timings of supply, type of industries etc.
- In the residential areas, the sewage flow rises by about 6 AM and reaches the maximum between 8 AM - 10 AM. The rate of flow then rises again.
- The relation b/w the max & the avg. rate of flow of sewage for residential area can be given by:

(i) Babbitt's formula:

$$Q_{max} = \frac{5 Q_{av}}{p^{0.2}}$$

Flow:-

dic & all methods

(ii) Harman's formula:

$$Q_{max} = \left(1 + \frac{14}{4 + p^{0.5}}\right) Q_{av}$$

Where,

Q_{max} - Max rate of flow

Q_{av} - Avg. rate of flow

P - Pop. in thousands

ends upon

- The first formula is restricted to max. value of $P=1000$ & a min. value of $P=1$.
- There is no limitations in 2nd formula.

☒ Shapes of Sewers :-

- (1) Circular Shaped
- (2) Egg Shaped

1) Circular Shaped :-

This is most commonly used.

Advantages :-

- (i) They are very easily manufactured
- (ii) It gives max. area for a given perimeter, and thus gives the greatest H.M.D when running full or half full.
- (iii) It is the most economical section
- (iv) It has uniform curvature all around

2) Egg Shaped Sewers :-

- Circular sewers are suitable only where variation in discharge is not large. They are suitable with separate sewage system.
- For combined system, egg shaped sewers (also called ovoid sewers) are more suitable.

Advantage :-

- (i) Has slightly higher vel. for low flows over than circular sewer of equal capacity.

Disadvantages :-

- (i) Unstable bcoz its small ends down
- (ii) It is more difficult to construct
- (iii) It is expensive

(iv) In not a Form

(a) St

(b) Ne

☒ Self

• A sel vel at

suspen the s

• Also it of the

taken

• It is r

vel thro

in se

• During

less th

• Hence,

atleas

☒ Shield

A/shield

borne

(iv) In the absence of adequate gradient, it is not self-cleansing.

Forme: \Rightarrow


- (a) Standard or Metropolitan Section
- (b) New shaped section.

* Self Cleansing Velocity and Slopes: \Rightarrow

- A self cleansing vel. may be defined as that vel. at which the solid particles will remain in suspension, without settling at the bottom of the sewer.
- Also it is that velocity at which even the ^{Entolott} scour of the deposited particles of a given size will taken place.
- It is not possible to maintain this self-cleansing vel. throughout the day because of fluctuations in sewage flow.
- During min flow of sewage, the vel. of flow is less than the self cleansing velocity.
- Hence, self cleansing vel. should be maintained atleast once in a day.

* Shield's Expression for self-cleaning velocity:—
A/shield, the vel. required to transport water borne solids is the self cleansing velocity

Diagram shows forces acting on Sediment



Consider a layer of unit sediment of unit length unit width and thickness t , deposited at the invert of the sewer. Let the slope of sewer be x . The drag force or the intensity of tractive force (T) exerted by the flowing water on a channel is given by:-

$$T = \gamma_w \cdot R \cdot S \quad \text{--- (1)}$$

where, γ_w = Unit wt. of water

R = Hydraulic radius of filled section

S = Slope of the invert or head loss per unit length

The submerged unit wt. of the sediment is

$$\gamma_{sub} = \gamma_w \left(\frac{G_s - 1}{1 + e} \right) = \gamma_w (G_s - 1) (1 - n) \quad \text{--- (2)}$$

G_s = Sp. Gravity of sediment

e = Void ratio, deposit

wt. of sediment is given by

$$W = \gamma_{sub} \times 1 \times 1 \times t$$

$$\therefore W = \gamma_w (G_s - 1) (1 - n) t \quad \text{--- (3)}$$

Friction

$R \approx$

where

when-

$\therefore \gamma_w \cdot k$

Putting

Chas. C. experiments

For S

Eq (2) g

will be

Now, for

or, V_s

or $\sqrt{V_s} =$

By η

Let the

$H_L =$

$\therefore S =$

Now v

on Sediment

Frictional Resistance R is given by

$$R \cong W \sin \alpha = \gamma_w (C_s - 1) (1 - n) t \cdot \sin \alpha \quad (4)$$

Where, α is the friction angle

When the sediment is just on the pt. of sliding,

$$\tau = R$$

$$\therefore \gamma_w \cdot k \cdot S = \gamma_w (C_s - 1) (1 - n) \cdot t \cdot \sin \alpha$$

Putting $(1 - n) \sin \alpha = k$, where k is the imp. char. of the sediment, to be determined by experiment.

$$S = \frac{k}{R} (C_s - 1) t \quad (5)$$

at of unit length deposited at

is slope of

is the intensity

the following

given by:-

(1)

filled section

or head loss per

unit length

sediment is

$-n$ — (2)

ent

deposit

— (3)

For Single grains, $d_s = \text{dia. of the grains} = t$

$$\therefore S = \frac{k}{R} (C_s - 1) d_s \quad (6)$$

Eq (6) gives the invert slope at which the vel. will be self-cleaning,

Now from Chezy's eqn.

$$V = C \sqrt{RS}$$

$$\text{or, } V_s = C \sqrt{R} \sqrt{\frac{k}{R} (C_s - 1) d_s} \quad \left[\because V = V_s \right] \quad (7)$$

$$\text{or } [V_s = C \sqrt{k (C_s - 1) d_s}] \quad (7)$$

By Darcy-Weisbach,

Let $H_L = \text{Head Loss}$

$$H_L = \frac{f L V^2}{2 g D} \quad (\text{where } D = \text{Pipe dia.})$$

$$\therefore S = \frac{H_L}{L} = \frac{f V^2}{2 g D}$$

$$\text{Now } V = C \sqrt{RS}$$

$$\therefore C\sqrt{R} = \frac{V}{15} = \sqrt{\frac{2gD}{f}}$$

For circular pipes running full, $R = \frac{D}{4}$

$$\therefore C\sqrt{\frac{D}{4}} = \sqrt{\frac{2gD}{f}}$$

$$\text{or, } C = \sqrt{\frac{8g}{f}} \quad \text{--- (8)}$$

Putting value of C in eq. (7)

$$\left[V_s = \sqrt{\frac{8\beta}{f}} (G_s - 1) g d_s \right] \quad \text{--- (9)}$$

Where,

V_s = Self cleansing vel.

β = Char. of solids flowing in the sewage

= 0.4 for initiating scour of clean

= 0.8 for full removal of sticky grit

f = Darcy-Weisbach friction factor = 0.03

G_s = Sp. Gravity of sediments/solids

= 2.65 for inorganic sediments

= 1.2 for organic

g = Gravitational acc. constant

d_s = dia. of solid particles

(1) Settling

• The scum out, settle and

and

• The

tail

const

• If on

the full

wait

Sche

(2) Alignment

• The

gradient

sight

Construction And Layout of Sewer Lines :-

(1) Settling out (2) Alignment & Gradient

(3) Excavation of trenches, timbering and dewatering

(4) Laying & Jointing (5) Testing and

(6) Backfilling

• A boni

wood

$$11, R = \frac{D}{4}$$

(8)

(9)


g in the sewerage
of clean
sticky grit
factor = 0.03
solids
vents
nt

Sewer Lines: →
Gradient
steering and

ry and


(+) Settling Out :->

- The settling out in the sewerage work is carried out starting from the tail end or cut-fall end, and proceeding upwards.
- The advantage of this is the utilization of tail sewers even during the initial period of construction.
- If on the contrary, this is done from head-end the function of the sewerage scheme has to wait till the completion of the entire scheme.



(9) Alignment and Gradient :->


- The sewers are laid to correct alignment and gradient with the help of boning rods and sight rails.



(a) Plan of the trench

- A boning rod or a traveller is a vertical wooden post suitably shod with shoe iron

and fitting fitted with a cross-head or tee.



- which
- (i) Stay
 - (ii) Ver
 - (v) Sh
 - Execa
 - dewater
 - (i) Ditet
 - (iii) Sha
 - (v) Vactu

• Its length is made equal to the ht of sight rail above the invert line of the sewer.

• The boring rod can move to and fro in the trench.

• Both

(3) Excavation of trench, timbering & dewatering:

- The work of excavation is usually carried out in open cutting.
- Wherever space is available, excavation is made with side slopes so that the slopes are stable.
- When the depth of trench exceeds 1.5 to 2m and when excavation is made with side vertical, it becomes necessary to support the side by sheeting bracing. This operation is known as timbering of trench.

- (4) Laying
Stone ware
- Pipes a
 - gradier
 - The R
 - bedding
 - advance
 - casted
 - in lig
 - The fir
 - curved f
 - Spigot
 - and i
 - stone

- (5) Hydran
Before
tested

38-head or ten

which may be done by :-

- (i) Stay bracing (ii) Box sheeting
- (iii) Vertical sheeting (iv) Runner sheeting
- (v) Sheet pile piling

• Excavation can be carried out by dewatering the subsoil water and is done by:

(b) Boring Rod

- (i) Ditches and sumps (ii) Well pt. system
- (iii) Shallow well system (iv) Deep well method
- (v) Vacuum method (vi) Electro-osmosis method.

The ht. of
line of

(4) Stone ware

Laying and jointing :->

and fro in

• Pipes are laid with sockets facing up the gradient on desired bedding.

• The R.C.C. pipes are laid in position over proper bedding, the type of which may be determined in advance, the abutting faces of the pipe being coated by means of a brush with bitumen in liquid condition.

ng & dewatering:
ually carried

• The finished joint should be protected and cured for at least 24 hours.

excavation is
he slopes are

• Spigot and Socket R.C.C. pipes are laid and jointed in a manner similar to stone ware spigot and socket pipes.

eds 1.5 to 3m.

with side
to support

(5) Hydraulic testing of pipes :-

This operation
renchy

Before backfilling, the pipe are hydraulically tested.

(6) Backfilling the trench: →

- Trenches should be backfilled immediately after the pipe is laid and tested.
- No water should be permitted to rise in the unbackfilled trenches.
- Filling is done at diff. stages, at each stage the filling should be well rammed, consolidated and completely saturated with water. and then only further line should be continued.
- Where trenches are in fields, the backfilling above the 600mm level is not tamped.

invert
end. (A
closed
the in
be su
ensure

(b) A
line a
line is
be obs
would
indicate

* Testing of Sewer lines: →

Following tests are performed:

- (1) Test for straightness and obstruction
- (2) Water test (3) Smoke test
- (4) Air test

2) Water
• This is
of the j
• This is
for the
• The sec
end wit
with

3) Smoke
• This is
in buildi
• The sor
tore be
machi

1) Test for Straightness and obstruction: →

- As Tested by two methods:
- (a) At the high end of the sewer (or drain), a smooth ball of dia. 13mm less than the pipe bore is inserted. If there is no obstruction in the form of yarn or mortar projecting through the joint, the ball will roll down the

immediately
ted.

ed to rise in

is, at each
is rammed,
treated with
ine should

the
level is

invert of the pipe and emerge at the lower end. (Alternatively a double disc or solid or closed cylinder 75mm less in dimension than the internal dimension of the sewer may be run through the stretch of the sewer to ensure that it is free from any obstruction)

(b) A mirror is placed at one end of the sewer line and lamp at the other end. If the pipe is straight, the full circle of light will be observed. If the pipe line is not straight, this would be apparent. The mirror will also indicate any obstruction in the pipe barrel.

rammed:
obstruction
it

struction:→

(are drain),
that the pipe
obstruction
projecting
call down the

2) Water Test:→

- This is done to find out the water tightness of the joints.
- This is carried out after giving sufficient time for the joints to set.
- The sewers are tested by plugging the upper end with a provision for an air outlet pipe with stop clock

3) Smoke test:→

- This is carried out for drainage pipes located in buildings.
- The smoke is produced by burning oil waste for paper etc in the combustion chamber of a smoke machine.

- The pipes are approved gas-tight by the smoke test conducted under pressure of 25 mm of water, maintained for 15 minutes after all traps/seals have been filled with water.

☒ Aims
sanit

(i) to

bu

(ii) to d

as f

(iii) to c

or th

(iv) to f

(v) to c

sys

4) Air testing:->

Air testing becomes necessary, particularly in large dia. pipes when the required quantity of water is not available for testing.

- It is done by subjecting the stretch of pipe to an air pressure of 100 mm of water by means of a hand pump.

☒ Maximum Velocity of flow or limiting Velocity

- At higher velocity, the flow becomes turbulent resulting in continuous abrasion of the interior surface of the sewer by the suspended particles.

☒ Princ
Plum

- Hence max. vel. of flow is also limited.

☒ Follow
efficie

- The max. vel. at which no such scouring action or abrasion takes place is known as non-scouring velocity.

1) The be
that,

- Such a vel. depends upon the material used for the construction of sewers.

In cas
be loc

- Abrasion is max. at the bottom of the sewer, because the sand etc. are heavy and travel along the invert.

2) The d
of the

3) All the
succe

bends
throu