

Code No: 156BC

JAWAHARLAL NEHRU TECHNOLOGICAL UNIVERSITY HYDERABAD

B. Tech III Year II Semester Examinations, August - 2022

HEAT TRANSFER
(Mechanical Engineering)

Time: 3 Hours

Max.Marks:75

Answer any five questions
All questions carry equal marks

- - -

- 1.a) Derive the general heat conduction equation in Cartesian Coordinate system.
b) A furnace wall consists of 200 mm layer of refractory bricks, 6 mm layer of steel plate and a 100 mm layer of insulation bricks. The maximum temperature of the wall is 1150°C on the furnace side and the minimum temperature is 40°C on the outermost of the wall. An accurate energy balance over the furnace shows that the heat loss from the wall is 400 W/m^2 . It is known that there is a thin layer of air between the layers of refractory bricks and steel plate. Thermal conductivities for the three layers are 1.52, 45 and $0.138\text{ W/m}^2\text{K}$ respectively. Find
i) How many millimeters of insulation brick is the air layer equivalent?
ii) What is the temperature of the outer surface of the steel plate? [7+8]
- 2.a) Derive the expression for temperature distribution under one dimensional steady state heat conduction through composite cylinder.
b) Define thermal conductivity, thermal diffusivity and thermal resistance and write their equations. [7+8]
- 3.a) Derive an expression for temperature distribution and heat transfer rate through fin insulated at the tip.
b) What are the assumptions for lumped capacity analysis? Discuss. [8+7]
4. Aluminum fins of rectangular profile are attached on a plane wall with 5 mm spacing. The fins have thickness $y = 1\text{ mm}$, $L = 10\text{ mm}$, and the thermal conductivity $K = 200\text{ W/m K}$. The wall is maintained at a temperature 200°C , and the fins dissipate heat by convection into the ambient air at 40°C , with heat transfer coefficient $h = 50\text{ W/m}^2\text{K}$. Determine the heat loss. [15]
- 5.a) Explain the Reynold and Colburn Analogy.
b) A plate of length 750 mm and width 250 mm has been placed longitudinally in a stream of crude oil which flows with a velocity of 5 m/s. If the oil has a specific gravity of 0.8 and kinematic viscosity of 1 stoke, calculate
i) Boundary layer thickness at the middle of the plate.
ii) Shear stress at the middle of plate and
iii) Friction drag on one side of the plate. [7+8]
- 6.a) Show by dimensional analysis for free convection, Nusselts number is a function of Prandtl number and Grasshoff number.
b) What are the advantages and limitations of dimensional analysis? Explain. [8+7]

- 7.a) Derive expression for effectiveness by NTU method for parallel flow heat exchanger.
- b) Steam at atmospheric pressure enters the shell of a surface condenser in which the water flows through a bundle of tubes of diameter 25 mm at the rate of 0.05 Kg/s. The inlet and outlet temperatures of water are 15⁰C and 70⁰C respectively. The condensation of steam takes place on the outside surface of the tube. If the overall heat transfer coefficient is 230 W/m²K, calculate the following using NTU method:
- The effectiveness of the heat exchanger
 - The length of the tube
 - The rate of steam condensation
- Take the latent heat of vaporization at 100⁰C is 2257 kJ/kg. [7+8]
- 8.a) Explain briefly the various regimes of saturated pool boiling by drawing the diagram.
- b) What is a black body? How does it differ from a gray body? Discuss in detail. [8+7]

---oo0oo---

downloaded from
StudentSuvidha.com